TVS Black Underlay

TECHNICAL INFORMATION

TVS GROUP
SPORT | FITNESS | PLAY | ACOUSTICS

TVS Black Underlay is a floor underlay for impact and sound reduction.

Material

Granules rubber with polyurethane bonding agent.

Appearance

Colour: black with some coloured spots
Surface: granule structure

Dimensions/Tolerances

Roll sizes: 10m x 1m x 3mm / 7m x 1m x 4.5mm (± 1.5%)
Available thickness: 3mm and 4.5mm (± 0.6mm),
other thicknesses available on request.

Physical Characteristics

Density: 760 - 860 kg/m³
Tensile strength: > 0.3 N/mm² (ISO 1798)
Elongation at break: > 30% (ISO 1798)
Service temperature range: -30°C to 120°C

Acoustic performance: in accordance with DIN EN ISO 10140-1,3:2021-09
ΔLw = 17dB – 3mm
ΔLw = 18dB – 4.5mm

Installation

Installation is to be carried out in accordance with TVS Black Underlay instructions.

NBS Source PARTNER

Product: TVS BLACK UNDERLAY
Revision: 1.0
Issued: 09/2025

T: +353 872 612061 | E: Ray@TVS-Group.ie | W: www.TVS-Group.co.uk
1 Daletree Mews | Ballycullen Road | Dublin D24 WY23
Head Office: Low Bay | Commerce Street | Carrs Industrial Estate
Haslingden | Rossendale | Lancashire | BB4 5JT | United Kingdom

TVS GROUP
SPORT | FITNESS | PLAY | ACOUSTICS
www.TVS-Group.co.uk